



Phone: 08 9250 3339
 Email: info@aquasportsmarine.com.au
 Website:

Boat Details

Price	POA	Boat Brand	Mercruiser
Model	8.2 Horizon DTS Inboard	Length	0.00
Year	2016	Category	Boat Engines and Outboards
Hull Style	Other	Hull Type	Other
Power Type	Power	Stock Number	0
Condition	New	State	Western Australia
Suburb	MIDVALE	Engine Make	

Description

One size doesn't fit all. Proven technology, rock-solid reliability and an unbeatable combination of performance and fuel efficiency.

Power & Performance.

High-displacement volume and premium MPI fuel injection combine to deliver outstanding acceleration, instant planing and smooth performance throughout the rpm band. Mercury® SmartCraft® Digital Throttle & Shift is standard, providing precision throttle response and effortless steering.

Fuel-Efficient.

Electronic multi-port injection (MPI) and standard Emissions Control Technology (ECT) combine to deliver precisely the correct amount of fuel for every stage of operation – no more, no less. The result is fuel economy that stretches your boat's range and your dollar.

Corrosion Protection.

The freshwater closed-cooling system (standard) dramatically limits potential corrosion. In fact, Mercury® is so bullish about the anti-corrosion technology built into these engines, we offer a standard four-year limited corrosion warranty in addition to the three-year limited factory-backed warranty.

Durable & Reliable.

Mercury's Engine Guardian continually monitors critical sensors for any sign of a problem and immediately takes action, while the water-cooled Cool Fuel delivery system prevents vapor lock. Rugged construction, including stainless-steel exhaust, ensures long-term, hassle-free operation.

HP / kW
 • 375 / 280

Maximum RPM (WOT)
 • 4200-4600

Engine type
 • V-8

Displacement (L)
 • 8.2

Bore and stroke
 • 4.47 x 4.00" / 113.5 x 101.6 mm

Compression ratio
 • 8.75:1

Recommended fuel
 • Unleaded Regular 87 Octane Minimum (R+M/2) or 90 RON 10% Ethanol Maximum

Fuel delivery system
 • Multi-point Electronic Fuel Injection (MPI)

Air induction
 • High inertia induction system

Ignition
 • Distributorless ignition with knock control

Alternator amp / Watt
 • 65 amp / 917 watt

Water drain system
 • Single point air actuated

Exhaust system

- Tuned runner exhaust manifolds with 316 stainless steel tubular dry joint elbows

Cooling system

- Brass sea water pump
- Closed cooling
- Long life 5-year antifreeze

Accessory drive system

- Auto-tensioner
- Serpentine belt

Recommended oil

- NMMA Certified FCW 25W-40 Synthetic Blend

Engine guardian system

- SmartCraft Engine Guardian

Dimensions (L x W x H)

- 35 x 33 x 24" / 878 x 838 x 610 mm

Weight (engine only)

- 990 lbs / 449 kg

Compatible drives

- ZF 63A Down Angle
- ZF 63IV V-Drive

Features

Horse Power (hp)

375

Engine Details

Horse Power

375