



Phone: 08 9250 3339
 Email: info@aquasportsmarine.com.au
 Website:

Boat Details

Price	POA	Boat Brand	Mercruiser
Model	Bravo Three (Sterndrive)	Length	0.00
Year	2016	Category	Boat Engines and Outboards
Hull Style	Other	Hull Type	Other
Power Type	Engine/Motor	Stock Number	0
Condition	New	State	Western Australia
Suburb	MIDVALE	Engine Make	Mercruiser

Description

Mercruiser Bravo Three Sterndrive - Efficient, easy to manoeuvre and an exciting performer, Bravo Three drives represent the complete package. * Single or twin installation for engines up to 525hp * Counter-rotating propellers provide agile handling. * Ultra-pure aluminium anodes and Mercury-exclusive MerCathode help prevent galvanic corrosion. *Excellent reverse handling and smooth, best-in-class shifting.

Maximum Power Capacity400 HP (295 kW)
 Lower Unit DesignExtended Length Strut
 Maximum Propeller Diameter2 X 16"
 Water Inlet LocationStrut
 Clutch TypeHigh-Strength Smooth-Shift Cone Clutch with F-N-R
 Available Gear Ratios1.81, 2.00, 2.20, 2.43:1
 Counter-RotationTwin Prop
 Upper Unit Gear SetPrecision Shimmed Assembly with Near-Net Forged Helical Gears
 Lower Unit Gear SetPrecision Shimmed Assembly Forged Bevel Gears with Twin Counter Rotating Propshafts for Bravo Three
 Propshaft MaterialHeat-Treated Stainless Steel
 Standard Exhaust OutletThrough Propeller
 Required Propeller HubNone for Bravo Three
 Recommended LubricantMercury High-Performance Gear Lube
 Monitoring SystemEngine-Mounted Lube Monitor w/Audio Warning or Engine Guardian®
 Corrosion Warranty3-Year, Limited
 Housing ConstructionCorrosion Resistant XK 360 Aluminum Low-Copper Alloy
 Corrosion ProtectionTri-Paint, Anodes & MerCathode® Electronic Corrosion Prevention
 Anode TypeUltra-Pure Aluminum Anodes or Magnesium Anode Kit
 Speedometer Pick-upIntegrated Into Lower Housing, Digital Output Optional
 Steering SystemSingle Cylinder Power Steering with Anti-Feedback
 Steering Range56° Range Stop to Stop, Digital Output Optional
 U-Joint TypePermalube® Virtually Maintenance-Free
 Power Trim SystemTwin-Cylinder Hydraulic Featuring Power Trim XD® Kick-up Return
 Typical Trim Range-2° to 14°
 Trim Limit SwitchAdjustable Limit Analog or Digital - Engine Dependant
 Trailer Limit51°
 Trim Hinge Pin DesignPermanently Lubricated - No Maintenance Required
 Hydraulic Trim LinesStainless Steel Braided Armor
 Drive CouplerGreaseable From Inside Boat
 Drive Weight148 lbs. (67 kg)

Features

Horse Power (hp)	400
------------------	-----

Engine Details

Engine Make	Mercruiser
Horse Power	525